

GET THE COMPETITIVE EDGE WITH REZNOR® UNIT HEATERS



**Looking for
a space-heating
solution for your
business, home
garage or workshop?**

Reznor unit heaters offer flexibility, reliability, efficiency, and performance, creating unparalleled comfort. Our industry-leading unit heater design will keep your space the right temperature so you can focus on the project at hand. Check out what makes our systems better than the rest.

ALLIES IN COMFORT

REZNOR® VERSUS THE REST

BRAND	UNIT HEATER CAPACITY						
REZNOR UDXC	30	45	60	75	100	125	
Approved for Residential Use	Yes	Yes	Yes	Yes	Yes	Yes	
Full Load Amps 115V	1.9	2.4	2.4	3.7	4.3	5.6	
Throw @ 10'	22'	33'	39'	52'	52'	60'	
External 24 V Wiring	Yes	Yes	Yes	Yes	Yes	Yes	
Single Burner	Yes	Yes	Yes	Yes	Yes	Yes	
External Gas	Yes	Yes	Yes	Yes	Yes	Yes	
Low Profile	Yes	Yes	Yes	Yes	Yes	Yes	
Thermal Efficiency %	82	83	83	83	83	83	
Competitor W's Unit	30	45	60	75	100	125	
Approved for Residential Use	Yes	Yes	Yes	Yes	Yes	Yes	
Full Load Amps 115V	3.7	3.7	2.5	2.5	4.7	4.2	
Throw @ 10'	25'	27'	36'	38'	42'	56'	
External 24 V Wiring	No	No	No	No	No	No	
Single Burner	No	No	No	No	No	No	
External Gas	No	No	No	No	No	No	
Low Profile	No	No	No	No	No	No	
Thermal Efficiency %	82	82	82	82	82	82	
Competitor X's Unit	30	45	60	75	90	106	120
Approved for Residential Use	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Full Load Amps 115V	3.2	3.2	4.1	4.1	6.4	6.4	6.4
Throw @ 10'	?	?	?	?	?	?	?
External 24 V Wiring	Yes	Yes	Yes	Yes	Yes	Yes	No
Single Burner	Yes	Yes	Yes	Yes	Yes	Yes	No
External Gas	Yes	Yes	Yes	Yes	Yes	Yes	No
Low Profile	Yes	Yes	Yes	Yes	Yes	Yes	No
Thermal Efficiency %	83	83	83	82	82	82	82
Competitor Y's Unit	30	45	60	75			
Approved for Residential Use	Yes	Yes	Yes	Yes			
Full Load Amps 115V	2.7	2.7	6.1	6.1			
Throw @ 10'	27	29	34	41			
External 24 V Wiring	Yes	Yes	Yes	Yes			
Single Burner	No	No	No	No			
External Gas	Yes	Yes	Yes	Yes			
Low Profile	Yes	Yes	Yes	Yes			
Thermal Efficiency %	83	83	83	83			
Competitor Z's Unit	30	45	60	75			
Approved for Residential Use	Yes	Yes	Yes	Yes			
Full Load Amps (115V)	3.2	3.2	4.1	4.1			
Throw @ 10'	28	28	28	35			
External 24 V Wiring	No	No	No	No			
Single Burner	No	No	No	No			
External Gas	No	No	No	No			
Low Profile	No	No	No	No			
Thermal Efficiency %	83	83	83	83			

FEATURES & BENEFITS

- Aesthetically pleasing design
 - Compact, space-saving construction to complement any given application
 - Distinctive design with removeable front face and beveled edge
 - Three-tone black and white corrosion and scratch-resistant paint scheme
 - Clean metal panels without any visible screws and fasteners
 - Tooled, rounded, vertical corners (models 30 to 125) and edges
- Power vented and separated combustion options in all sizes
- High efficiency levels
- Industry-leading low amp draw, emission levels, and sound levels
- Variety of options
 - 409 or 316 stainless-steel heat exchangers
 - 409 stainless-steel burners
 - Two-stage gas valve and thermostat
- TCORE® titanium stabilized heat exchanger
- "G" terminal and circuit board design allow for fan only operation
- Single burner design (regardless of capacity)
- Ease of gas and altitude conversion (one spring, one orifice)
- External gas connection
- External low voltage wiring connections
- Models UDXC/UBXC feature:
 - Green operating light recessed on bottom of unit visible from floor
 - Error codes on circuit board for troubleshooting
 - Hinged and safety-cable for service access door
 - QR code inside and outside of unit – unit specific
 - WiFi Stat compatible
 - Field convertible power vent unit to sealed combustion
 - Unit mounted on/off switch
 - Approved for residential garages and workshops (UDXC sizes 30 to 125 only)
- Up to 93% efficiency on model UEZ

COMPETITIVE WARRANTY

With 130+ years of heating expertise and innovation, we stand by our industry-leading unit heaters. That is why we offer one of the longest warranties in the business:

5 YEARS ON PARTS **10 YEARS ON HEAT EXCHANGER**

Call your Reznor® Rep to find a product that works for you 800.695.1901.

Visit reznorhvac.com for more information on the Reznor® product line.



Intertek

